Precast Concrete Restrooms

10/8/2015 City of Gallatin

1.0 Introduction

The City of Gallatin is seeking bids for (2) **Precast Concrete Restrooms** for the Leisure Services Department. Bids will be due on October 21st 2015 at 2:00 pm in a sealed envelope clearly marked: (2) **Precast Concrete Restrooms.**

2.0 Technical Requirements

Lavout:

- 1. Four individual rooms, each to include (1) Water closet and (1) Lavatory
- 2. One of the four rooms to be ADA compliant
- 3. Utility chase with rear access

Interior:

- 1. Walls and ceiling: Insulation package with FRP paneling, White
- 2. Floor: Smooth concrete painted with epoxy, Gray
- 3. Chase walls: Stud with FRP paneling, White

Exterior:

- 1. Walls: Concrete with simulated brick finish, sealed and stained, choice of color
- 2. Roof: Concrete with simulated metal roof, sealed and stained, choice of color

Doors:

- 1. 3'0" x 7'0" 18 gauge steel insulated w/ 16 gauge cast-in-place frames
- 2. 3 hour fire rating
- 3. NRP stainless steel hinges
- 4. Mortise lever locksets
- 5. Aluminum thresholds
- 6. Hydraulic door closers
- 7. Galvanized, primed and painted

Electrical:

- 1. 48" 32W dual bulb florescent fixtures throughout (operated by switches)
- 2. GFCI duplex receptacle in chase
- 3. Tankless water heaters
- 4. 125 amp exterior breaker panel
- 5. Exterior light with photocell on front (optional at rear of building)
- 6. Concealed wiring in restroom areas, surface mounted in chase

HVAC:

- 1. Exhaust fans operated with light switch in restrooms
- 2. Louvers in restroom doors
- 3. Electric heater in plumbing chase
- 4. Mini split A/C units for restrooms

Plumbing:

- 1. Water closet fixtures vitreous china with concealed manual flush valves
- 2. Lavatory fixtures vitreous china with single lever faucet
- 3. Waste, vent and water lines pre-plumbed to floor openings
- 4. Hose bibs in chase and each restroom
- 5. All Piping PVC and PEX
- 6. Sewer and water stub-ups required

Accessories:

- 1. Grab bars 18 gauge, type 304 stainless steel
- 2. Dual toilet paper holders, stainless steel
- 3. Fixed tilt mirrors, ADA compliant
- 4. C-fold paper towel holders, stainless steel

Quality Assurance:

- International building code 2009
- National electrical code 2011
- Florida building code 2007
- ACI-318-2008, "Building code requirements for reinforced concrete"
- ASCE-7-2008 "Minimum design loads for building and other structures"
- UL-752 Test method level four (4) for bullet resistance certified by an independent structural engineer
- Concrete reinforcing institute, "Manual of standard practice"
- PCI design handbook 6th edition
- Steel construction manual AISC 360-05
- ADA standards 28 CFR part 36 1994

Structural Specifications:

- Concrete: Steel-reinforced, polypropylene fiber reinforced, 5000 PSI minimum 28-day compressive strength, air-entrained (ASTM C260)
- Walls and roof: 2 hour fire rated
- Walls 4", floor 6", roof 4" (Concrete gable style roof)
- Loadings: Wind 140 MPH, roof 60 PSF, floor 250 PSF
- Reinforcing steel: ASTM A615, grade 60 unless otherwise indicated
- Reinforcing fiber: Polypropylene fiber, fiber mesh @ 1.5 pounds per cubic yard
- Caulking: All joints between panels shall be caulked on the exterior and interior surface of the joints. Caulking shall be SIKAFLEX-1A elastic sealant or equal
- Panel connections: All panels shall be securely welded together with ¼" thick steel brackets. Steel is to be of structural quality, hot-rolled carbon complying with ASTM A283, grade C. Cast-in anchors used for panel connections to be Dayton-Superior #F-63, or equal

These are minimum specs required. Equal or better would be accepted.

3.0 Vendor Requirement

- Meet above specifications. See Drawings
- Price to include delivery, FOB to Gallatin TN 37066.
- Provide specification sheet for products being bid.

4.0 Evaluation of Proposals

The City of Gallatin will award the contract to lowest responsible and responsive bidder meeting specifications, quality, and performance standards pursuant to the Municipal Purchasing Act of 1983. Response will be based on the following factors:

- Completeness of response
- Cost
- Vendor track record, including references
- Quality of service
- Quality of product

5.0 Contract Award

The City of Gallatin reserves the right to reject any or all proposals and to waive any informality found therein. The City of Gallatin will award a contract based on evaluations described above. In the event that the lowest bidder is not available at time of need, the city reserves the right to go with the next lowest bidder.

6.0 Question Submissions

Facility: Long Hollow Golf Course

Attn: David Brown 210 Albert Gallatin Ave Gallatin TN 37066

Telephone: 615-642-1283

7.0 Proposal Submission

ALL SUBMISSIONS MUST BE SEALED AND CLEARLY MARKED

Precast Concrete Restrooms

BID DUE DATE: October 21st 2015 @ 2:00pm

Proposals shall be directed to the attention of:

Finance Department

Attn: J.R.Smith, Jr


132 West Main Street

Gallatin, TN 37066


Telephone: 615-451-5963

PRICE SHEET: PRICES ARE TO BE GOOD FOR 60DAYS

Precast Concrete	e Restrooms (2) \$	
Name of Company:		_
Address:		_
Telephone:		-
Signature:		-
Print Name:		-
Title:		
Date:		



FLOOR PLAN



FLOOR OPENINGS